

TITLE OF THE INVENTION

CODE READING APPARATUS, ENTERTAINMENT SYSTEM AND
RECORDING MEDIUM

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Application No. 2001-062090 filed March 6, 2001, the
entire contents of which are incorporated herein by
reference.

10 BACKGROUND OF THE INVENTION

1. Field of the Invention

2010086422-030102
15 This invention relates to a code reading apparatus
adapted to optically read an optically readable code on
a recording medium, the recording medium recording data
as the optically readable code, and also to a recording
medium for recording such a code. The present
invention also relates to an entertainment system using
such a code reading apparatus.

2. Description of the Related Art

20 Various code reading apparatuses adapted to
optically read a code from a recording medium on which
records data as an optically readable code such as
a one-dimensional or two-dimensional bar code are
known.

25 Information output from such a known code reading
apparatus of the above identified type is unequivocally
defined for a code reading operation of the operator.

Therefore, when such a code reading apparatus is applied to an entertainment system such as a game machine, the latter allows the user to play only simple games. Similarly, educational equipment provided with such a code reading apparatus allows the user to use only simple learning processes. Thus, such apparatus inevitably have a limit in terms of making them enjoyable to operators and exciting their interest.

BRIEF SUMMARY OF THE INVENTION

In view of the above identified circumstances, it is therefore an object of the present invention to provide a code reading apparatus comprising a randomness providing means for providing the code read by the apparatus with randomness so that the apparatus may give a surprise to the operator for an operation performed on it by the operator in order to make it suitably applicable to an entertainment system or educational equipment.

It is another object of the present invention to provide an entertainment system that comprises a code reading apparatus according to the invention and can give the user who is playing on the system a wide variety of enjoyments by utilizing the randomness provided by the code reading apparatus.

According to a first aspect of the present invention, there is provided a code reading apparatus comprising:

10086422-030407

a reading section for optically reading
an optically readable code from a recording medium on
which records data as the optically readable code;

an output section for performing an output based
5 on the outcome of the code reading operation of the
reading section; and

a randomness providing section for providing the
outcome of the code reading operation of the reading
section with randomness, thereby providing the output
10 of the output section based on the outcome of the code
reading operation with randomness.

According to a second aspect of the invention,
there is provided an entertainment system comprising:

an operating section for receiving an operation
15 command from the user;

an output section for performing at least one of
a display output and a sound output adapted to vary
according to the operation command received by the
operating section;

20 a reading section for optically reading an
optically readable code from a recording medium on
which records data as the optically readable code; and

a randomness providing section for providing the
outcome of the code reading operation of the reading
25 section with randomness at the time of the output
operation of the output section on the basis of the
outcome of the code reading operation of the reading

10086422.030102

section, thereby providing the output of the output section based on the outcome of the code reading operation with randomness.

According to a third aspect of the invention,
5 there is provided a recording medium comprising:

a part recording data as an optically readable code; and

a part recording no code, wherein

the data recorded as a code includes information
10 to be provided with randomness and a plurality of pieces of information to be used for providing randomness; and

the output of the information to be provided with randomness is varied according to the piece of
15 information for providing randomness selected from the plurality of pieces of information as a result of an operation of reading the code by a code reading apparatus reading.

According to a fourth aspect of the invention,
20 there is provided a recording medium comprising:

a part recording data as an optically readable code; and

a part recording no code, wherein

the data recorded as a code includes information
25 to be provided with randomness and a program adapted to select a motion out of a plurality of motions; and

one of the motions is selected to vary the output

10086422-030102
20100722

of the information to be provided with randomness as a result of an operation of reading the code by a code reading apparatus reading.

According to a fifth aspect of the invention,
5 there is provided a recording medium comprising:

a part recording data as an optically readable code; and

a part recording no code, wherein

the data recorded as a code includes information
10 to be provided with randomness and a program adapted to handle program parameters; and

the program parameters is varied to vary the operation of the program and also the output of the information to be provided with randomness as a result
15 of an operation of reading the code by a code reading apparatus reading.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be
20 learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

25 The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and, together

2010086422-030102

with the general description given above and the detailed description of the embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a schematic block diagram of a code reading apparatus according to a first embodiment of the invention;

FIG. 2 is a schematic illustration of a code that can be picked up by a single shot of image pickup operation;

FIG. 3 is a schematic block diagram of the main body of the code reading apparatus;

FIG. 4 is a schematic illustration of a code that can be recorded on a recording medium;

FIG. 5 is a schematic illustration of information that can be obtained by the functions blocks of the main body of the code reading apparatus;

FIG. 6 is a schematic illustration of parameters relating to brightness information that can be obtained from a piece of multi-value image information;

FIG. 7 is a schematic illustration of parameters relating to pixel attributes that can be obtained from a piece of binarized image information;

FIG. 8 is a schematic illustration of parameters relating to position/shape that can be obtained from a piece of code position/shape information;

FIG. 9 is a schematic illustration of parameters relating to a code data that can be obtained from

a piece of code data information;

FIG. 10 is a schematic illustration of parameters relating to restored information that can be obtained from a piece of restored information;

5 FIG. 11 is a schematic illustration of an ordinary two-dimensional bar code;

FIG. 12 is a schematic illustration of an ordinary one-dimensional bar code;

10 FIG. 13 is a schematic illustration of a known code comprising a plurality of blocks;

FIG. 14 is a schematic illustration of a block of a known dot code, showing its configuration;

15 FIG. 15 is a schematic block diagram of a binarization section of the code reading apparatus, illustrating its configuration and pieces of information that can be obtained by it;

20 FIG. 16 is a schematic block diagram of a data reading position determining section of the code reading apparatus, illustrating its configuration and pieces of information that can be obtained by it;

FIG. 17 is a schematic block diagram of the main body including an address detecting section of the code reading apparatus;

25 FIG. 18 is a schematic block diagram of a data restoring section of the code reading apparatus, illustrating its configuration and pieces of information that can be obtained by it;

20086422-09102

5 FIG. 20 is a schematic illustration of a recording medium and the code reading apparatus main body, illustrating a manual operation of holding the code reading apparatus main body and scanning the recording medium;

FIG. 22 is a schematic illustration of an image
picked up by an image pickup operation conducted at
15 a certain time;

FIG. 24 is a schematic illustration of a method of detecting a parameter relating to the relative moving speed;

25 FIG. 26 is a schematic illustration of an image
picked up by an image pickup operation conducted at
a certain time;

FIG. 27 is a schematic illustration of the image picked up by the next image pickup operation;

FIG. 28 is a schematic illustration of the relationship between the code recorded on a recording medium and the image pickup regions of which are to be picked up by a code reading apparatus in each image pickup operation;

FIG. 29 is a schematic illustration of a parameter relating to a meandering motion;

FIG. 30 is a schematic illustration of a parameter relating to the directions of mutual movements and the number of times of mutual movements;

FIG. 31 is a schematic illustration of the positional relationship between the scanning guide and the image pickup device when they are assembled together;

FIG. 32 is a schematic illustration of a method for acquiring a parameter relating to the magnification of a lens;

FIG. 33 is a schematic illustration of a method for acquiring a parameter relating to the position of the scanning guide;

FIG. 34 is a schematic illustration of a method for acquiring a parameter relating to a lighting condition;

FIG. 35 is a schematic illustration of a method for acquiring a parameter relating the distortion of

a focusing lens;

FIGS. 36A to 36C are views showing a table of parameters effective for providing randomness;

FIG. 37 is a schematic illustration of masking
5 cards and data cards;

FIG. 38 is a schematic illustration of the masking card laid on the data card;

FIG. 39 is a schematic illustration of the randomness added to the outcome of a code reading
10 operation according to the read out control code;

FIG. 40 is a schematic perspective view of the code reading apparatus of the first embodiment of the invention as applied to an entertainment system;

FIG. 41 is a schematic illustration of a recording
15 medium to be used as a playing card;

FIG. 42 is a schematic illustration of a logical format of a code;

FIG. 43 is a flow chart of the operation of an entertainment system;

FIG. 44 is a schematic illustration of data stored
20 in the ROM of an application program storing cartridge operating as a game cartridge;

FIG. 45 is a flow chart of an operation of the CPU of a program processing apparatus operating as portable
25 game machine main body in the entertainment system;

FIG. 46 is a flow chart of another operation of the CPU of the program processing apparatus;

FIG. 47 is a flow chart of still another operation of the CPU of the program processing apparatus;

FIG. 48 is a schematic illustration of the data stored in the ROM of the application program storing cartridge of a code reading apparatus according to a
5 second embodiment of the invention;

FIG. 49 is a schematic illustration of a method for acquiring a parameter relating the speed; and

FIG. 50 is a schematic illustration of the data
10 stored in the ROM of the application program storing cartridge of the code reading apparatus according to the second embodiment as used for acquiring a parameter relating the speed.

DETAILED DESCRIPTION OF THE INVENTION

15 Now, the present invention will be described in greater detail by referring to the accompanying drawings that illustrate preferred embodiments of the invention.

[1st Embodiment]

20 Referring to FIG. 1, a code reading apparatus according to a first embodiment of the invention comprises a code reading apparatus main body 100, an application program storing cartridge 200 and a program processing apparatus 300. The main body 100 includes
25 an illumination LED 101, a focusing lens 102, an image pickup device 103, an A/D converter 104, a binarization circuit 105, a binarization memory 106, a CPU

(microcomputer) 107, a timing generator 108,
an illumination drive circuit 109, operation button
110, a medium sensor 111, a system ROM 112, a work RAM
113, a bus bridge 114 and a power supply section 115.

5 The application program storing cartridge 200 includes
a program ROM 201, a data RAM 202, an environment
sensor 203 and a connector 204. The program processing
apparatus 300 includes a connector 301, a CPU 302,
a ROM 303, a RAM 304, an operating section 305,
10 a liquid crystal display (LCD) 306 and a sound output
section 307.

The illumination LED 101 in the code reading
apparatus main body 100 is used to illuminate an
optically readable code 401 on a recording medium 400,
15 the recording medium 400 recording data as the
optically readable code 401. Light reflected by the
code 401 is picked up by the image pickup device 103 by
way of the focusing lens 102. If an entire image of
the code 401 cannot be picked up by a single shot of
20 the image pickup device 103, it can be picked up by
manually scanning, i.e., by moving the main body 100
relative to the recording medium 400 or by holding the
recording medium 400 and moving it relative to the main
body 100. If an entire image of the code 401 can be
25 picked up by a single shot of the image pickup device
103 as shown in FIG. 2, such a manual scanning
operation is not necessary. It is also possible to set

10086422-030102

the recording medium 400 to automatically move relative to the main body 100 by a mechanical means.

5 The analog video signal output from the image pickup device 103 as a result of the image pickup operation is converted into a multi-value image signal by the A/D converter 104 and then into a binarized image by the binarization circuit 105, which is then stored in the binarization memory 106.

10 The CPU 107 processes the binarized image stored in the binarization memory 106 and restores the original data recorded as a code 401. The CPU 107 also controls the timing of driving each of the components of the main body 100, including the image pickup device 103, the A/D converter 104, the binarization circuit 15 105 and the binarization memory 106, by controlling the timing generator 108. Additionally, the CPU 107 controls the threshold value of binarization of the binarization circuit 105 by giving it information for selecting a value as the threshold value and also the 20 light emitting operation of the illumination LED 101 by transmitting it a light emitting pulse signal to the illumination drive circuit 109.

The operation of controlling the components by the CPU 107 is started by operation command information 25 issued in response to the operation button 110 being operated. Alternatively, it may be so arranged that the operation of controlling the components by the CPU

2010050-2249800T

107 is started in response to a detection signal issued from the medium sensor 111 operating on the recording medium 400. Namely, the operation button 110 and the medium sensor 111 may be provided alternatively, or may
5 be provided both.

The system ROM 112 is a non-volatile memory storing the operation program of the CPU 107 and various data. The work RAM 113 is a memory for temporarily storing various data while the CPU 107 is
10 in operation.

The bus bridge 114 is provided to coordinate the system bus of the CPU 107 and the bus in the application program storing cartridge 200. As a result of a coordinated operation of the bus bridge 114,
15 the CPU 107 can transmit the restored data and various other data to the application program storing cartridge 200.

As will be described in greater detail hereinafter, the CPU 107 is also adapted to detect
20 parameters including one for brightness from the multi-value image information from the A/D converter 104 and transmit them to the application program storing cartridge 200 by way of the bus bridge 114. Additionally, the CPU 107 is also adapted to transmit
25 various parameters obtained in the course of operation of processing the binarized image information from the binarization memory 106 and restoring the original data

10086422-030402

The power supply section 115 is used to feed power to the components of the main body 100. It may alternatively be so arranged that power from the power sources of different components of the main body 100 is fed to the program processing apparatus 300 by way of the application program storing cartridge 200.

15 The environment sensor 203 is adapted to detect
various environmental values including temperature,
humidity, time, location and atmospheric pressure.
A GPS or the location acquisition service of a PHS may
be used for detecting the current location of the
20 system.

The connector 204 is used to electrically connect the connector 301 of the program processing apparatus 300 and the application program storing cartridge 200. It may typically be an edge connector having a plurality of contacts arranged along the edge of a substrate. The bus in the application program storing cartridge 200 and the system bus in the program

processing apparatus 300 are connected to each other by means of the connectors 204 and 301. As a result of the connection, the CPU 302 of the program processing apparatus 300 can read the application program stored in the program ROM 201, the data and the parameters stored in the data RAM 202 and the values detected by the environment sensor 203.

Although not shown in FIG. 1, power is supplied to the components of the application program storing cartridge 200 from the program processing apparatus 300.

On the other hand, the ROM 303 of the program processing apparatus 300 is a non-volatile memory for storing the operation program of the CPU 302 and various data. The RAM 304 is a memory for temporarily storing various data while the CPU 302 is in operation.

The operating section 305 comprises user buttons for issuing a command for a desired operation to the CPU 302. The LCD 306 is used to display image data under the control of the CPU 302. The sound output section 307 is used to output sound data under the control of the CPU 302.

When the program processing apparatus 300 is designed to operate for a video game machine, the LCD 306 is replaced by a terminal for connecting a television monitor (not shown) and a video signal generator (not shown) for converting image data into

an image signal (video signal or RGB signal) under the control of the CPU 302.

10086422 030102
20750 2248807

5 In a code reading apparatus having the above described configuration, the CPU 302 of the program processing apparatus 300 changes the display output of the LCD 306 and outputs sound from the sound output section 307 according to the application program stored in the program ROM 201 of the application program storing cartridge 200 and the operation performed at
10 the operating section 305. Whenever necessary, the main body 100 reads the data recorded on the recording medium 400 as the optically readable code 401, and the outcome of the reading operation is stored in the data RAM 202 of the application program storing cartridge
15 200, and the CPU 302 of the program processing apparatus 300 reads out the outcome of the operation of reading the code and outputs respectively an image and/or a sound from the LCD 306 and/or sound output section 307 according to the outcome of the code
20 reading operation.

25 While the above operation is similar to that of any known code reading apparatus, the embodiment of code reading apparatus additionally detects parameters, which will be described in greater detail hereinafter, in the main body 100 or the application program storing cartridge 200 and stores them in the data RAM 202 during the code reading operation, and then the CPU 302

of the program processing apparatus 300 provides the outcome of the code reading operation with randomness according to the stored parameters.

Now, the means for providing randomness and some
5 of the specifics of such randomness will be discussed below.

Firstly, the means for providing randomness will be described.

FIG. 3 is a block diagram illustrating the
10 operation of the code reading apparatus main body 100 along with some of its functional features. Referring to FIG. 3, the image input section 121 of the main body 100 comprises the illumination LED 101, the focusing lens 102, the image pickup device 103 and the A/D
15 converter 104 and picks up the optically readable code 401 to obtain a multi-value image. Then, the multi-value image is binarized by binarization section 122 that corresponds to the binarization circuit 105, the binarization memory 106 and the CPU 107. The data
20 reading position determining section 123 that also corresponds to the CPU 107 determines the data reading points of the binarized image and obtains code position/shape information. Then, the data reading section 124 that also corresponds to the CPU 107 reads
25 the image data located at the data reading points to obtain the code data. Thereafter, the data restoring section 125 that also corresponds to the CPU 107

decodes the code data and obtains the restored information, or the original data.

Assume that the code 401 recorded on the recording medium 400 is such as the one shown in FIG. 4,

5 including code indexes 402 indicating that it is a code 401 and data 403 expressed by using black and white squares that respectively represents "1"s and "0"s.

Then, the multi-value image information obtained by the image input section 121, the binarized image
10 information obtained by the binarization section 122, the code position/shape information obtained by the data reading position determining section 123, the code data information obtained by the data reading section 124 and the restored information obtained by the data
15 restoring section 125 are such as those shown in FIG. 5.

The multi-value image information, the binarized image information, the code position/shape information, the code data and the restored information are stored
20 in the data RAM 202 of the application program storing cartridge 200 by the CPU 107 by way of the bus bridge 114. Subsequently, any of them is read out by the CPU 302 of the program processing apparatus 300 so that the output data of the restored information, that
25 used to be recorded as code 401 may be provided with randomness.

The parameters of the maximum brightness, the

minimum brightness or the average brightness as shown
in the upper right graph of FIG. 6 can be obtained from
the multi-value image information by detecting the
brightness of each pixel. Also, the parameters of the
5 black mode, the white mode or the local minimum as
shown in the lower right graph of FIG. 6 can be
obtained by detecting the frequency of occurrence of
each brightness level. Furthermore, it is also
possible to arrange a plurality of predetermined
10 regions in the picked up image as shown in the lower
left frame of FIG. 6 and obtain the parameters of the
average brightness of each of the regions. As a matter
of course, it is also possible to obtain the parameters
of the maximum brightness, the black mode, etc. of each
15 predetermined region.

The parameters of the frequency of occurrence of
a white pixel and that of a black pixel as shown upper
right in FIG. 7 can be obtained from the binarized
image information. It is also possible to obtain the
20 parameters of pixel attribute indicating that the pixel
at a predetermined position is a black pixel or a white
pixel as shown lower right in FIG. 7. Furthermore, it
is also possible to obtain the parameters of pixel
distribution in each predetermined region indicating
25 the percentage of area of black pixels and that of
white pixels in each predetermined region as shown
lower left in FIG. 7.

The parameters of the position, the size and the shape of each code component as shown upper right in FIG. 8 can be obtained from the code position/shape information. It is also possible to obtain the

5 parameters of the positions where the data are to be read as shown lower right in FIG. 8. Furthermore, it is also possible to obtain the parameters of the number of detected code components such as code indexes 402 as shown lower left in FIG. 8.

10 The parameters of the number of "0"s, that of "1"s, that of inverted "0"s and "1"s, data length, the number of "0"s and "1"s in a predetermined length, those of consecutive "0"s, those of consecutive "1"s and so on as shown in FIG. 9 can be obtained from the

15 code data information.

Finally, the parameters of the type of information (image, text, sound, etc.), the length of information (number of bytes, time, etc.) and the contents of information (the producer who prepared the information,

20 the ID of the code, that of the recording medium, etc.) as shown in FIG. 10 can be obtained from the restored information.

The code 401 may be a two-dimensional code as shown in FIG. 11 or a one-dimensional bar code as shown

25 in FIG. 12.

In the case of a two-dimensional code as shown in FIG. 11, code indexes 402 are arranged at three of the

10086422.030102

four corners of the code and data cells 403A are recorded as data in data region 404. If there are a large number of data cells 403A, positioning indexes 405 are arranged between two code indexes 402 in order to improve the positioning accuracy.

In the case of a one-dimensional bar code as shown in FIG. 12, code indexes 402 are arranged at the opposite ends of the code, and bars are recorded between them as data 403.

A code comprising a number of blocks may be used as shown in FIG. 13. Each block of such a code can be prepared by adding address information to the code as shown in FIG. 11.

A dot code comprising a number of blocks as disclosed in U. S. Patent No. 5,866,895 is also known. As shown in FIG. 14, each block contains block data 404A, markers 402A, pattern dots 405A and a block address pattern 406. The block data 404A is a region in which dots corresponding to data to be recorded are arranged two-dimensionally in a predetermined manner. The markers 402A are arranged at the four corners of the block and used to locate reading reference points for reading each dot (data dot 403B) of the block data 404A. Each marker 402A is formed by arranging a predetermined number of black dots. The pattern dots 405A are a group of isolated dots arranged between the markers 402A and used to accurately locate the reading

reference points. The block address pattern 406 is arranged also between the markers 402A for the purpose of identifying the block and contains the address of the block and an error detection or correction code.

5 As shown in FIG. 15, the binarization section 122 may be made to comprise a brightness information detecting section 122A, a threshold value control section 122B and a binary value determining section 122C. Naturally, the brightness information detecting section 122A and the threshold value control section 122B are arranged in the CPU 107 and the binary number determining section 122C is arranged in the binarization circuit 105.

10 Thus, the brightness contained in the multi-valued image information from the image input section 121 is detected by the brightness information detecting section 122A, and the threshold value control section 122B determines the threshold value for binarization, using this brightness information (e. g., an intermediate value between the maximum and minimum brightness levels is used as the threshold value). Then, the determined threshold value information is sent to the binary value determining section 122C of the binarization circuit 105 as information to be for selecting a threshold value and used for the operation of binarizing the multi-value image information from the image input section 121.

With the above described configuration, the brightness information detecting section 122A provides brightness information to make it possible to extract parameters such as the maximum brightness, while the
5 threshold control section 122B provides threshold value information.

When a code containing positioning indexes as shown in FIG. 11 or FIG. 14 is used, the data reading position determining section 123 is made to comprise
10 a code index detecting section 123A, a positioning index detecting section 123B and a data reading position computing section 123C as shown in FIG. 16.

Thus, the code index detecting section 123A detects the image of the code indexes 402 (markers
15 402A) from the binarized image from the binarization section 122 and the positioning index detecting section 123B detects the image of the positioning indexes 405 (pattern dots 405A) arranged between the code indexes 402 (markers 402A). Then, the data reading position
20 computing section 123C computationally determines the data reading positions in the binarized image according to the detected locations of the code indexes and those of the positioning indexes.

With the above described arrangement, information
25 on the positions, the number and the shape of the code indexes can be obtained from the code index detecting section 123A while information on the positions,

10086422.030102

the number and the shape of the positioning indexes can be obtained from the positioning index detecting section 123B.

5 If a code comprising a number of blocks as shown in FIG. 13 or FIG. 14 is used, the code reading apparatus main body 100 needs to further comprise an address detecting section 126 as shown in FIG. 17, the address detecting section 126 being formed by the CPU 107.

10 Then, in parallel with the operation of the data reading section 124 for reading the data at the positions where the data is to be read as determined by the data reading position determining section 123, the address detecting section 126 detects the addresses of the blocks containing the data. Subsequently, the data
15 restoring section 125 restores the original data by rearranging the data read by the data reading section 124 according to the addresses detected by the address detecting section 126.

20 With this arrangement, it is possible to obtain address information from the address detecting section 126.

Normally, code data is modulated and/or error correction data is added thereto. When such a code is
25 used, the data restoring section 125 needs to comprise a demodulating section 125A, an error correction information extracting section 125B and an error

10085422-030102

correcting section 125C as shown in FIG. 18.

As disclosed in U. S. Patent No. 5,896,403, when data is recorded as an optically readable code 401, the code is generally modulated. Therefore, the demodulating section 125A that is provided to handle modulated data demodulates the data read by the data reading section 124. Then, the error correction information extracting section 125B extracts the error correction information from the data demodulated by the demodulating section 125A and the error correcting section 125C corrects the errors in the data demodulated by the demodulating section 125A according to the extracted error correction information.

With the above described arrangement, the demodulating section 125A provides data information after demodulation and the error correction information extracting section 125B provides error correction information including the number and the positions of corrected errors.

Normally, the code 401 is typically recorded along an edge of a card-shaped recording medium 400 as shown in FIG. 19. When the code 401 is manually scanned, the operator holds the recording medium 400 and moves it along the slit 131 arranged in the code reading apparatus main body 100 in order to make the image pickup device 103 pick up an image of the entire code 401 into the image pickup region 132 of the image

10086422-030402

pickup device 103 that is located at a predetermined position in the slit 131.

Alternatively, it may be so arranged that the code 401 is recorded on a sheet-shaped recording medium 400 and the operator holds the pen-shaped code reading apparatus main body 100 that is connected to the application program storing cartridge 200 by way of a cable 500 and moves it along the code 401, as shown in FIG. 20, in order to pick up the code 401 in an image pickup region (not shown) arranged at the top of the main body 100.

When the code is manually scanned in the manners as described above, the following additional information can also be acquired.

When a code 401 that contains address information as described above by referring to FIG. 13 or 14 and in which addresses are arranged sequentially as shown in FIG. 21 is scanned relative to the image pickup region 132 of the code reading apparatus main body 100, a speed parameter can be obtained as relative movement information. With this arrangement, when an image as shown in FIG. 22 is obtained by an image pickup operation and an image as shown in FIG. 23 is obtained by a subsequent image pickup operation, the amount of relative movement of the code is obtained by the positions of the positioning indexes or the address information in a manner as illustrated in FIG. 24.

10086422-030102

Then, the relative moving speed of the code can be calculated from the amount of relative movement and the time interval of the two image pickup operations.

Additionally, an acceleration parameter can be obtained by differentiating the calculated relative moving speed.

When a code 401 that contains address information as described above by referring to FIG. 13 or 14 and in which addresses are arranged sequentially is scanned by means of the pen-shaped code reading apparatus main body 100 as shown in FIG. 25, a meandering parameter can be obtained as relative movement information. With this arrangement, when an image as shown in FIG. 26 is obtained by an image pickup operation and an image as shown in FIG. 27 is obtained by a subsequent image pickup operation, it is found that the code 401 moved relative to the image pickup region 132 in a manner as shown in FIG. 28. Therefore, as shown in FIG. 29, the amount of movement, or meander, between the two picked up images can be determined by comparing the positions of the positioning indexes or the addresses of the two picked up images.

When a code 401 that contains address information as described above by referring to FIG. 13 or 14 and in which addresses are arranged sequentially, it is also possible to obtain a parameter for the direction of relative movement or the number of times of relative

movement of the code can be obtained as relative movement information. The direction of relative movement of the code can be determined by variation of the detected positions of the positioning indexes or by whether the addresses are detected in rising order or in falling order. Additionally, if addresses are detected in the order of "1, 2, 3, 4, 5, 6, 7, 8, 7, 6, 5, 4, 5, 6, 5, 6, 7, 8, 9, 10, ..." as shown in FIG. 30, it is found that the code 401 is subjected to relative movement in a manner as indicated by the arrows in FIG. 30 sequentially in the order of the encircled numbers. In other words, the direction of relative movement and the number of times of relative movement of the code 401 can be obtained.

Parameters relating to the code reading apparatus can also be obtained in a manner as described below.

When the code reading apparatus main body 100 is of the type illustrated in FIG. 19 and adapted to read the code 401 on the card-shaped recording medium 400 as the latter is moved in the slit 131, the illumination LED 101, the focusing lens 102 and the image pickup device 103 are arranged in such a way that the image pickup region 132 is located vis-à-vis the code 401 when the recording medium 400 is moved while it is being pressed against the bottom of the slit 131 operating as scanning guide 133 as shown in FIG. 31.

Then, as shown in FIG. 32, a parameter relating to

the magnification of the focusing lens 102 can be
obtained from the picked up image typically by
utilizing the information on the positions at which the
code indexes 402 are read and detecting the length of
the diagonals of the block of the code 401, provided
that the size of the code 401 is given in advance.

A parameter relating to the position of the
scanning guide 133 can be obtained by detecting the
distance from an end of the picked up image to each of
the code indexes 402.

Similarly, a parameter relating to the lighting
condition of the illumination LED 101 can be obtained
by detecting brightness information (information on
the average brightness of each predetermined area) as
shown in FIG. 34 and a parameter relating to the
distortion of the focusing lens 102 can be obtained by
detecting the shape of the blocks of the code, the
length and the width of the blocks for example, as
shown in FIG. 35.

The types of parameters that can be detected by
a code reading apparatus according to the invention and
the methods for detecting parameters are described
above. FIGS. 36A to 36C are views showing a table
summarily showing effective parameters that can be used
for providing randomness. More specifically, FIGS. 36A
to 36C show detected pieces of information, parameters
that can be acquired from the detected pieces of

information and if each of the acquired parameters is effective as a "parameter relating to the code reading operation", "parameter relating to the way of reading the code", "parameter relating to the recording medium" and/or "parameter relating to the code reading apparatus".

10 The "parameter relating to the way of reading the code" as used herein refers to a parameter by which the outcome of a code reading operation as the parameter varies as a function of the manner how the operator operates if the recording medium is not changed.

15 The "parameter relating to the recording medium" as used herein refers to a parameter by which the outcome of a reading operation can be controlled as a function of the recording medium recording the code. In other words, the outcome of the reading operation varies depending on the recording medium that is subjected to the reading operation if the reading operation is not changed. The "parameter relating to the code reading

20 apparatus" as used herein refers to a parameter by which the outcome of a reading operation can be controlled as a function of the code reading apparatus. In other words, the outcome of the reading operation varies depending on the code reading apparatus that is used for the reading operation if the reading operation is not changed and the recording medium is not changed.

Thus, code reading environment parameters

10086422-030102

including those for temperature, humidity, time,
position, atmospheric pressure, etc. are obtained by
detecting the environment information. These
parameters are particularly effective when used as
5 "parameters relating to reading" or "parameters
relating to the code reading apparatus". It is also
possible to obtain parameters relating to the time
required for the power source to rise to the normal
power level and the supply voltage as environment
10 information. Such parameters are particularly
effective when used as "parameters relating to the code
reading apparatus".

On the other hand, the parameters for the maximum
brightness, the minimum brightness, the average
15 brightness, the brightness distribution, the average
brightness of the predetermined region, etc. are
obtained by detecting the multi-value image
information. These parameters can be used as
"parameters relating to the way of reading the code"
20 because they may represent the suspended condition and
the inclination, if any, of pen-shaped code reading
apparatus main body 100. They can also be used as
"parameters relating to the recording medium" because
some of them may represent the reflectivity of the
25 recording medium 400. Furthermore, they can also be
used as "parameters for the code reading apparatus"
because they may represent the intensity of light

10086422.030102

and the shading of the illumination LED 101 and
the sensitivity of the image pickup device 103.

A parameter for the recording ink density of the code
401 can be obtained by calculating the ratio of the
5 maximum brightness and the minimum brightness from
the multi-value image information and the obtained
parameter can be used as "parameter relating to
the recording medium". Additionally, a parameter for
the brightness of some of the components of the code,
10 for example the brightness of the code indexes or that
of the background, can be obtained from the multi-value
image information. Such a parameter can be used as
a "parameter relating to the recording medium" and/or
"parameter relating to the code reading apparatus".

15 Threshold value parameters can be obtained by
detecting the threshold information. Because such
parameters vary, due to the recording ink density and
the intensity of light of the code reading apparatus,
they can be used as "parameters relating to the
20 recording medium" and/or "parameters relating to the
code reading apparatus".

On the other hand, parameters for the number of
black pixels, that of white pixels, the ratio of white
pixels to black pixels, etc. can be obtained by
25 detecting the binarized image information. These
parameters can be used as "parameters relating to the
recording medium" because they depend on the design of

10086422.030102

the code and its surroundings. Particularly, the parameter for the number of black pixels can be used as a "parameter relating to the code reading apparatus" because it relates to the intensity of light and the shading of the illumination.

Furthermore, parameters for the detected positions of the code indexes (positioning indexes), the number of detected code indexes (positioning indexes), the size of the code indexes, the shape of the code indexes, the center of gravity/the geometrical center of the code indexes, the distance separating two neighboring code indexes (the size of the code and that of the block), the positional relationship of the code indexes (the shape of the code and that of the block), information on missing code indexes, etc. can be obtained by detecting the information on the positions, the number and the shape of the code indexes (positioning indexes). These parameters are particularly effective if used as "parameters relating to the code reading operation" and "parameters relating to the way of reading the code". Additionally, since the recording ink density and the magnification of the focusing lens 102 can vary, parameters for the detected positions, the size and the shape of the code indexes, the center of gravity/the geometrical center of the code indexes, the distance separating two neighboring code indexes, the positional relationship of the code

indexes and the information on missing code indexes can be used as "parameters relating to the recording medium" and "parameters for the code reading apparatus".

5 Furthermore, parameters for the addresses and, if the addresses are provided with an error correction code, parameters for the number of corrected address errors (missing address data), the positions of the corrected address errors, and addresses missing
10 information can be obtained by detecting the address information. Address parameters may include one indicating if address "10" is detected or not or one indicating the number of the frame where address "10" is detected (the elapsed time in ms after the start of
15 the code reading operation). Such address parameters can be particularly effective if used as "parameters relating to the code reading operation" and "parameters relating to the way of reading the code". The parameter for the number of corrected address errors
20 (missing address data) represents information on the number of address errors and varies depending on the scanning speed, the meandering of the code reading apparatus and/or the stains on the recording medium and hence can be used as "parameter relating to the code
25 reading operation", "parameter relating to the way of reading the code" and/or "parameter relating to the recording medium". The parameter for the positions of

10080422-030102

the corrected address errors represents information on the address errors, if any, and hence can be used as a "parameter relating to the recording medium". The parameter for information on missing addresses represents that are missing probably because the way of reading the code was wrong, the state of the recorded code was bad, the focusing lens 102 was smeared and/or the image pickup device 103 was defective and hence can be used as "parameter relating to the code reading operation", "parameter relating to the way of reading the code", "parameter relating to the recording medium" and/or "parameter relating to the code reading apparatus".

Parameters for the positions at which data are to be read, the number of black dots, the number of white dots, the ratio of black dots to white dots, the data length, the number of read blocks, etc. are obtained from the code data information. These parameters represent the recorded code, so they are effective when used as "parameters relating to the recording medium". Since the code reading apparatus can meander, the parameter for the positions at which data are to be read can effectively be used as a "parameter relating to the code reading operation" and/or "parameter relating to the way of reading the code".

Additionally, the parameter for the number of read blocks can be used as "parameter relating to the code

reading operation" and/or "parameter relating to the way of reading the code" because all the blocks may not be read when the scanning speed is too high.

When the demodulated data information is detected,
5 parameters respectively representing the number of "1"s, that of "0"s and the ratio of "1"s/"0"s can be obtained. These parameters are particularly effective when used as "parameters relating to the recording medium" because they are produced from the code.

10 On the other hand, when the error correction information is detected, parameters for the number of corrected errors (missing data) and the positions of corrected errors can be obtained. Since the parameter for the number of corrected errors (missing data) can
15 vary depending on the scanning speed and the condition of the recording medium, it can effectively be used as a "parameter relating to the code reading operation", "parameter relating to the way of reading the code" and/or "parameter relating to the recording medium".
20 The parameter for the positions of corrected errors can vary significantly depending on the recording condition of the code, so it can be effectively used as the "parameter relating to the recording medium".

When the restored information is detected,
25 parameters for the ID, the producer (the person who prepared the code), the type of information, the recording time, the amount of data, etc. can be

1008642 "030102

obtained. Since these parameters vary depending on the information recorded as the code, they can be effectively used as "parameters relating to the recording medium".

5 When the relative movement information is detected, parameters for the moving speed, the moving direction, the number of movements, etc. can be obtained. These parameters are particularly effective as "parameters relating to the code reading operation" and "parameters relating to the way of reading the code". Parameters for meandering movements can also be obtained and effectively used as "parameters relating to the code reading operation" and "parameters relating to the way of reading the code" when a pen-shaped code reading apparatus main body 100 is used. Furthermore, the parameters for meandering movements can effectively used as "parameters relating to the recording medium" when a code reading apparatus main body 100 of the type for reading the code by receiving a card-shaped recording medium 400 in slit 131 is used because such meandering movements can be caused by cutting errors of the cut edges of card-type recording medium 400 and as "parameters relating to the code reading apparatus" because such meandering movements can be caused by assembling errors of the scanning guide 133 that is to be held in contact with the cut edges of card-type recording medium 400 and the image pickup device 103.

10086422"030402

It is also possible to obtain a parameter for the time period from the time the operation button 110 is operated or a command is input in response to the detection of a recording medium by the recording medium sensor 111 to the time a predetermined position of the code is obtained. Such a parameter can be used as "parameter relating to the code reading operation" and "parameter relating to the way of reading the code".

It should be noted that each circle in FIGS. 36A to 36C indicate that the detected information relating to the circle is particularly effective for that parameter and the information may also be used as a "parameter relating to the code reading operation", "parameter relating to the way of reading the code", "parameter relating to the recording medium" and/or "parameter relating to the code reading apparatus" if no circle is shown for the information.

A masking card as shown in FIG. 37 may be used as a "parameter relating to the way of reading the code".

A plurality of masking cards 400M that are identical in terms of dimensions and shape are provided with a slot 411 arranged at a position corresponding to the data code 401D on the card-shaped recording medium 400 and a control code 401C recorded at a side of the slot 411. The control codes 401C of all the masking cards 400M are identical in terms of size and position so that the masking cards 400M are not discriminable to

varies according to the combination of masking card and data code.

Now, how the outcome of a code reading operation is provided with randomness by such randomness providing means will be discussed below.

Assume that the above embodiment of the code reading apparatus is that of an entertainment system.

Referring to FIG. 40, the program processing apparatus 300 is provided as a portable game machine main body that is contained a low-profile housing 311, and the operating section 305 and the LCD 306 of the program processing apparatus 300 are exposed at a main surface (shown in FIG. 40) of the housing 311. The housing 311 is provided at an upper position of the rear side thereof with an insertion slot 312 for receiving an application program storing cartridge 200 that is a game cartridge. On the other hand, the application program storing cartridge 200 that is a game cartridge is integrally formed with the code reading apparatus main body 100 that is arranged at the rear side of the cartridge opposite to the side that is led into the insertion slot 312. When the cartridge 200 is loaded into the program processing apparatus 300 that is the game machine main body, the slit 131 for receiving the recording medium 400 is exposed from the top of the housing 311.

On the other hand, the recording medium 400 is

1005422 030102

provided as a playing card as shown in FIG. 41 that carries, on one of the main surfaces thereof, a graphic display region 431, a power data storage region 432 and an optically readable code 401 operating as data.

5 If the recording medium 400, or the playing card, has an oblong rectangular profile, the graphic display region 431 is arranged in the upper half of the card or in an upper half area larger than a half of the entire surface area of the card, and a character image of
10 an animal, a person or an imaginary monster may be printed there. The kind, design or pattern of the character image printed in the graphic display area 431 may vary from card to card in order to represent the characteristic of the playing card. It may be
15 an image of a character (a character of the protagonist, a character of the party or the adversary or any character whose image can be an object of collection) that appears on the game screen when the game program stored in the program ROM 201 of the
20 application program storing cartridge 200 is executed. A number of such playing cards (e. g., 30 to 40 cards) may be collected into a set (which is referred to as a "starter kit"), each carrying, with arbitrary
25 probability, an image of a funny or cute character that is an object of collection, and put up for sale with or without the code reading apparatus main body 100 and application program storing cartridge 200. A set of

10086432-030402
201009-224800

duplicates of a small number of different cards (which is referred to as "expansion pack") may also be put up for sale. When the code reading apparatus main body 100 and the application program storing cartridge 200 are provided separately, the starter kit may be sold with the application program storing cartridge 200.

The power data storage region 432 is used to display power data (also referred to as attribute data) of the character shown in the graphic display region 431. The power data are visually (recognizably) expressed by using printed letters, symbols and/or numerals. They may include: the name and number of the character; the weapons and/or the magical techniques that the character can use; and the strength, the power, the hit-point and the offensive and defensive capabilities of the character as expressed by letters, symbols and/or numerals. If necessary, a symbol indicating the value of the recording medium 400 showing the character (rareness mark) may also be printed in the power data storage region 432.

The code 401 is arranged at least along a side of the recording medium 400 operating as playing card in a less remarkable way. The code 401 may be arranged along two opposite sides of the recording medium 400 without overlapping the graphic display region 431 and the power data storage region 432 or alternatively along three or four sides of the recording medium 400

so as to surround the graphic display region 431 and the power data storage region 432. The data recorded as code 401 include: power data described in the power data storage region 432 including the identification
5 code of the character and data on the techniques, the weapons and other features that can be used for the game as expressed in terms of words and/or sentences (or texts); and additional data (e. g., sound data and dot data or graphic data showing the character).

10 It may be appreciated that such power data and additional data may be selectively used depending on the game to be played. The additional data may include sound data that may be the voice of the character, if the character is a human being, or the crying or
15 roaring sound of the character, if the character is an animal or a monster, and additional power data other than the visually recorded power data (items with which the character can exert magical power and/or hidden power that makes the character invincible for
20 a predetermined period of time).

For example, if the game is that of capturing or raising an imaginary monster, an image of the monster is drawn in the graphic display region 431 and the data (power data and/or additional data) recorded as code
25 401 include data on the skills of the monster, the roaring sound of the monster, data on the evolving monster, explanation data describing the characteristic

10086422-030102

aspects of the monster as expressed in terms of words
and/or sentences (letters or texts) and data translated
the explanation data. If the game is that of a sports
game including a baseball or soccer match game and
5 the character is a (baseball or soccer) player,
a photographic image of the character is shown in the
graph display region 431 and the data recorded as code
401 include the team name, the uniform number and the
age of the player as well as the achievement data of
10 the player (the batting average, the number of home
runs, the RBIs, the number of steals and running
ability if the player is a baseball field player, the
earned run average, the number of strikeouts and the
given runs if the player is a baseball pitcher, the
15 physical potential, the number scores and the number of
assists if the player is a soccer player). If the game
is a role playing game or an action game, the character
is a person, an animal or an imaginary living thing and
the data recorded as code 401 may include data
20 expressing characteristic properties including data on
the life, the power and the potential of the character
as well as the items that the character can use
(weapons, protectors, magic, etc.)

If a mini-game is played by combining and using
25 a plurality of playing cards, or recording mediums 400,
it is possible to divide the program for mini-game and
make the playing cards, or the recording mediums 400,

record the parts produced by dividing the program along with sequence data as code 401. In such a case, a plurality of different programs may be prepared for the mini-games so that the program part recorded on the playing card as code 401 may be decided depending on the kind of the playing card (the kind of monster (Water type, Fire type, Grass type, etc.)).

A plurality of different data may be appropriately combined and recorded as code 401.

As shown in FIG. 42, in the code 401, the attributes for determining the type and amount of data and the card ID for identifying the recording medium 400 may be recorded as a header so that the data of each type of recorded data may be identified and reflected onto the electronic game.

Such recording mediums 400 may be collected as playing cards (trading cards) because of the charm of the graphic images printed on the respective graphic display regions 431 of the cards. Furthermore, the cards may be used for a card game by utilizing the information recorded in the power data recording region 432.

Now, an example where the electronic game is that of capturing or raising an imaginary monster and an image of the monster printed on the recording medium 400 as a playing card appears in the electronic game will be described below.

Then, the program ROM 201 of the application
program storing cartridge 200, or the game cartridge,
stores a program adapted to modify the electronic game
by using the data read from the code 401 of the
5 recording medium 400 as a playing card and at least one
of the "parameters relating to the code reading
operation", the "parameters relating to the way of
reading the code", the "parameters relating to the
recording medium" and the "parameters relating to
10 the code reading apparatus" obtained in a manner as
described above. If the data expressing characteristic
properties represent items that enhance the potential
of the character (weapons, magical techniques, etc.),
the program ROM 201 may store a program that allows the
15 character to use one or more than one of the items as
selected on the basis of the parameters. If the data
expressing characteristic properties represent a dot
(graphic or image) data of a character other than the
character who figure in the game, the program ROM 201
20 may store a program for animating dot (or graphic) data
of the character as read from the recording medium 400,
or the playing card, in various different ways and a
process for animating the dot data may be selected on
the basis of the parameters. If, on the other hand,
25 the data expressing characteristic properties are
those prepared by dividing a program for a number of
mini-games on a predetermined data unit basis and

stored in a number of recording mediums 400, or playing cards, the program ROM 201 may store a control program with which one of the mini-programs is selected on the basis of the parameters, parts of the selected mini-game are read from the recording mediums 400 and assembled together according to a predetermined sequence for the purpose of playing the mini-game and the assembled mini-game is executed.

FIG. 43 is a flow chart of the operation of such an entertainment system.

Referring to FIG. 43, as the power switch (not shown) of the program processing apparatus 300, or the portable game machine main body, is turned on, the CPU 107 of the code reading apparatus main body 100 starts operating according to the program stored in the system ROM 112. Firstly, it determines if an insertion of a recording medium 400, or a playing card, is detected or not according to the output of the medium sensor 111 (or instruction information by operating the operation button 110 is input or not) (Step S11). If no card insertion is detected, it is held in a standby state until the medium sensor 111 detects a recording medium 400, or a playing card.

As a recording medium 400, or a playing card, is inserted into the slit 131, the medium sensor 111 detects the recording medium 400, or the playing card. Then, in response to the detection, the CPU 107 drives

the illumination LED 101 to turn on (Step S12).

Then, the operator moves the recording medium 400 so as to make the edge thereof where a code 401 is arranged

slide on the scanning guide 133 at the bottom of the

5 slit 131 (Step S13). The CPU 107 sequentially operates

the image pickup device 103 so as to shoot the code 401

on the recording medium 400 (Step S14) and pick up an

image thereof, then the binarization circuit 105 so as

to binarize the outcome of the image pickup operation

10 and subsequently the binarization memory 106 so as to

store the binarized image (Step S15). Thereafter, as

pointed out earlier, it determines the positions at

which the data are to be read on the basis of the

binarized image (Step S16) and the data at those

15 positions are actually read (Step S17) so that the

original data are restored (Step S18) and stored in the

data RAM 202 of the application program storing

cartridge 200, or the game cartridge. The parameters

obtained in the course of carrying out the above steps

20 are also stored in the data RAM 202.

Then, it is determined if the movement of the recording medium 400, or the playing card, is

terminated or not (or the input of the instruction

information by the operation of the operation button

25 110 is disappeared or not) (Step S19). If it is found

that the medium sensor 111 is still detecting the

recording medium 400, the CPU returns to Step S14 to

10086422-030102

repeat the Steps S14 through S19 until the recording medium 400 is no longer detected. In other words, the Steps S14 through S19 are repeated until the data of all the blocks recorded as code 401 are read.

5 When it is found in Step S19 that the movement of the recording medium 400, or the playing card, is terminated, the illumination LED 101 is turned off (Step S20). Then, the data read from the recording medium 400 as a sheet of the playing card, and the
10 parameters obtained in the course of the above data reading operation that are stored in the data RAM 202 are sequentially read out by the CPU 302 of the program processing apparatus 300, or the code reading apparatus main body, and temporarily stored in the RAM 304
15 (Step S21). Thereafter, the CPU 302 analyzes the data read out and stored in the RAM 304 (Step S22) and carries out a processing operation for the game program that is being executed properly in order to provide it with randomness that reflects the read out and analyzed
20 data according to the read out and analyzed data and the program stored in the program ROM 201 of the application program storing cartridge 200, or the game cartridge (Step S23). If the data recorded as code 401 is text data, the letters or the sentences read out
25 from the code 401 are displayed on the LCD 306 and the processing operation for providing randomness may be such that the font may be changed and/or some of the

words may be inflected according to the parameters
(Step S23A). If the data recorded as code 401 is
graphic (or dot) data for displaying a character, the
graphic data is displayed on the LCD 306 and the
5 processing operation for providing randomness may be
such that the intervals separating the graphic data may
be changed according to the parameters (Step S23B).
If the data recorded as code 401 is sound data for
a roaring sound of the monster, the sound data is D/A
10 converted and output from the audio output section 307
as sound and the processing operation for providing
randomness may be such that the duration of the sound
output may be changed according to the parameters
(Step S23C).

15 Now, how randomness is provided according to the
parameters will be described in greater detail by way
of an example where the parameter for the number of
corrected errors is used.

Assume that, as shown in FIG. 42, the recording
20 medium 400, or the playing card, bears data written in
a logical format as code 401 and the data read out from
the code 401 is corrected for errors if it contains
errors, so that it is warranted that the data may be
correctly and reliably read out unless they contain
25 errors excessively.

The data section contains image data and, if the
image data are provided with an animation pattern as

an additional factor of image data, an animated image is displayed on the LCD 306 according to the animation pattern. The number of corrected errors (error rate) as detected at the time of reading the code 401 from the recording medium 400 is told by the CPU 107 to the CPU 302 by way of the data RAM 202 and the RAM 304.

Additionally, as shown in FIG. 44, the program ROM 201 of the application program storing cartridge 200, or the game cartridge, stores combinations of error rates and animation patterns. If animation pattern [0] is a weak animation and animation patterns [1], [2], [3], ... become stronger in an ascending order, a game where the character grows stronger as the card is used more often will be realized.

When the program ROM 201 stores such animation patterns, the CPU 302 of the program processing apparatus 300, or the portable game machine main body, produces animation in a manner as shown in the flow chart of FIG. 45 according to the game program stored in the program ROM 201 of the application program storing cartridge 200, or the game cartridge.

Referring to FIG. 45, the CPU 302 reads out the character data that are read from the code 401 and the error rate E, which is a parameter acquired in the course of the processing operation for obtaining the character data, from the data RAM 202 of the application program storing cartridge 200 and stores

them in the RAM 304 in a step corresponding to the
above described Step S21 (Step S111). It will be
appreciated that, in this example, the operation of
analyzing the read out data in Step S22 is omitted
5 because it is known that the data that are read from
the code 401 are character data according to the
information stored in the program ROM 201.

Then, the CPU 302 sets "0" in an internal counter
 α (not shown) as initial value (Step S112) and
10 subsequently compares the error rate $[\alpha]$ shown on the
internal counter α and the error rate E stored in the
RAM 304 to see if the error rate E is not smaller than
the error rate α or not (Step S113).

If the error rate E is smaller than the error rate
 α , the CPU 302 raises the reading of the internal
15 counter α to "+1" (Step S114). Then, it determines if
the reading of the internal counter α after "+1" is set
has exceeded the number n of combinations of error
rates and animation patterns stored in the program ROM
20 201 or not (Step S115) and, if it is found that the
reading has not exceeded the number n, it returns to
Step S113. If, on the other hand, it is found that
the reading has exceeded the number n, it displays
the error display and/or outputs an error notifying
25 sound in a predetermined manner.

If it is found that the error rate E is not
smaller than the error rate $[\alpha]$, YES is replied to the

10086422-030102

question of Step S113 and the animation pattern $[\alpha]$
corresponding to the error rate $[\alpha]$ is read out from
the program ROM 201 of the application program storing
cartridge 200 and displayed with the character data
5 stored in the RAM 304 to display an animated image
(Step S116).

In this way, while a single set of character data
is read out from the code 401 on the recording medium
400, or the playing card, they are animated in one of
10 different ways as one of the animation patterns is
selected according to the detected error rate E.

Animation can be realized by the game program
itself without providing animation patterns as shown
FIG. 44. If such a case, the CPU 302 operates
15 according to the game program stored in the program ROM
201 in a manner as shown in FIG. 46.

Referring to FIG. 46, the CPU 302 reads out the
character data that are read from the code 401 and the
error rate E that is a parameter acquired in the course
20 of the processing operation for obtaining the character
data from the data RAM 202 of the application program
storing cartridge 200 and stores them in the RAM 304
(Step S121).

Then, it compares the error rate E stored in the
25 RAM 304 with two error rate constants β_1 , β_2 given by
the game program stored in the program ROM 201 (Step
S122).

If the error rate E is not greater than the first error rate constant β_1 , the animation 1 subroutine of the game program stored in the program ROM 201 is executed (Step S123) and the first animation is displayed by using the character data stored in the RAM 304.

If, on the other hand, the error rate E is greater than the first error rate β_1 but not greater than the second error rate β_2 , the animation 2 subroutine of the game program stored in the program ROM 201 is executed (Step S124) and the second animation is displayed by using the character data stored in the RAM 304.

Finally, if the error rate E is greater than the second error rate β_2 , the animation 3 subroutine of the game program stored in the program ROM 201 is executed (Step S125) and the third animation is displayed by using the character data stored in the RAM 304.

In this way, while a single set of character data is read out from the code 401 on the recording medium 400, or the playing card, they are animated in one of different ways as one of the motions of the program is selected according to the detected error rate E .

It is also possible to change the moving speed of the animated figure, or the frame rate of the animation being displayed, as a function of the error rate E , as shown in FIG. 47.

Referring to FIG. 47, firstly, the CPU 302 reads

out the character data read from the code 401 and
the error rate E that is a parameter acquired in
the course of the processing operation for obtaining
the character data from the data RAM 202 of the
5 application program storing cartridge 200 and stores
them in the RAM 304 (Step S131).

Then, it divides the constant F given from the
game program stored in the program ROM 201 by the error
rate E stored in the RAM 304 and stores the quotient in
10 the internal register as a rewriting interval (Step
S132). It sets the initial reading of the internal
counter T to "0" and also that of the internal counter
A to "0" (Step S133).

After that, the CPU 302 raises the internal
15 counter T to "+1" and raises the internal counter A to
"+1" (Step S134). Then, it determines if the reading
of the internal counter A is smaller than the rewriting
interval stored in the internal register (Step S135).

Thereafter, if the reading of the internal counter
20 A is smaller than the rewriting interval, it displays a
screen image by using the character data stored in the
RAM 304 (Step S136). Subsequently, it determines if
the reading of the internal counter T is not smaller
than 150 or not (Step S137) and, if not, it returns to
25 Step S134.

If, on the other hand, it is determined in Step
S135 that the reading of the internal counter A is not

smaller than the rewriting interval, the CPU 307
rewrites the image of the character data stored in the
RAM 304 (Step S138). Then, after resetting the
internal counter A to "0" (Step S139), the CPU 302
5 proceeds to Step S136, where it displays a screen image
by using the rewritten character data.

In this way, the above steps of processing
operation are repeated until the reading of the
internal counter T in Step S137 exceeds 150.

10 In other words, the image is rewritten once every
one thirtieth of a second and the rewriting interval
indicate at which of the images produced by the
rewriting operation conducted once every one thirtieth
of a second the character data are modified. The
15 rewriting interval is reduced as the error rate E
raises so that the image is rewritten frequently and
hence the image of the animation moves more quickly.
In the flow chart, the processing operation ends after
looping 150 frames, or 5 seconds.

20 In this way, while a single set of character data
is read out from the code 401 on the recording medium
400, or the playing card, the operation of the program
is modified by using the detected reading error rate E
as program parameter and one of a plurality of
25 animations is effected.

The animation pattern data or the program for the
motions shown in the flow chart of FIG. 45, 46 or 47

10086422-030102

may be stored in the code 401 on the recording medium
400 instead of the program ROM 201, and transferred to
the RAM 304 by way of the data RAM 202 for operation.
Then, the operation is same as that described above and
5 only the program ROM 201 needs to be replaced by the
data RAM 202 as shown in parenthesis in FIG. 44.

When the animation pattern data or the program is
recorded as part of the code 401, the code 401 may
occupy a relatively large region on the recording
10 medium 400. Then, the remaining regions including the
graphic display region 431 and the power data recording
region 432 may need to be made relatively small.
However, regardless of this disadvantage, this
arrangement is highly advantageous in that the
15 animation pattern or the program is not limited to it
stored in the program ROM 201 of the application
program storing cartridge 200, or the game cartridge,
and can be variously changed by changing the data
stored as part of the code 401 to make the
20 entertainment, or the game, highly flexible.

The parameter of the error rate may be used in
a different way as described earlier to provide the
outcome of reading the code with randomness.

As described above in detail, this first
25 embodiment provides an advantage that the outcome of
reading a code is same if condition including a
recording medium, a operator, a code reading apparatus,

10085422-030402

or a code reading environment is same and identical,
and a various outcomes with randomness are obtained if
the condition is not same and identical.

For example, in an entertainment system of using
5 trading cards to be collected by collectors, the cards
carrying an optically readable code to be read so as to
display an image obtained by code reading operation on
a display, it is a known method to make the program
generate a random number each time a code is read and
10 modify the game according to the random number, in
order to diversify the game. However, with this
method, while the game may be diversified easily
because the program is modified, anybody can reproduce
a certain displayed image in time by repeating the
15 reading operation of the code. Then, the game quickly
becomes boring. On the other hand, a certain displayed
image cannot be reproduced repeatedly if they are based
on a random number. In other words, the code reading
operation needs to be repeated for a huge number of
20 times in order to reproduce a same image to frustrate
the user.

On the other hand, the codes printed on cards may
vary due to the printing operation, and missing data
may occur due to stains or degradation of the print.
25 Additionally, the code reading apparatuses may vary
mechanically and electronically, due to the
manufacturing process, therefore, the code reading

apparatus may exhibit different characteristics from apparatus to apparatus in terms of values selected for regulating the unevenness and for reading operations. Furthermore, the environmental conditions upon a reading operation may vary from apparatus to apparatus in terms of ambient temperature and external light entering the code reading apparatus. Still further, the way the card is moved through the code reading apparatus, in terms of direction, speed and hand wagging, as well as the sequence a plurality of cards are inserted if a plurality of cards are used, may vary from user to user.

The above described embodiment utilizes these characteristics that become available in the operation of reading the code, in order to provide the game with randomness, so that the entertainment system may change in various ways. In other words, the entertainment system is provided with changes particular to the system by utilizing the differences in the card, the code reading apparatus, environmental conditions and operators to make the system really enjoyable.

Some of the advantages of the embodiment are listed below.

1: Trading cards are an object of collection and exchange. The owners of such cards can also enjoy exchange of information concerning such cards. This embodiment can produce various different outcomes from

a single operation of reading the code printed on
a card by utilizing variances attributable to the code.
In other words, cards carrying the same code may vary
from card to card so that the enjoyment of exchanging
and collecting cards can be greatly enhanced.

2: The entertainment system can be so arranged
that the outcomes of a single operation of reading the
codes printed on cards vary from card to card depending
on the size of the dot codes and the brightness
information. Then, the printing effect and the density
of ink at the time of printing a code may be positively
and easily varied to produce cards that are different
from each other in terms of effects of operation,
without raising the printing cost and changing the form
plate.

3: This embodiment can produce diverse outcomes
by utilizing variances in the code reading apparatus.
In other words, the code reading apparatus of a user
may perform differently from that of his or her
friends. Then, the user can have his card read by the
code reading apparatus of the friend and vice versa to
enjoy the outcomes by comparing them. If the code
reading apparatuses are provided with a
telecommunications feature, the outcome of the
operation of the friend's apparatus of reading his or
her own card can be stored in his or her own apparatus.

4: This embodiment utilizes the habits of

10086422 030106
201009 224800

the user in using the code reading apparatus to read a card. Therefore, the outcome of an operation that the code reading apparatus read the code printed on a card may vary from person to person. For example, a monster drawn on a card is animated, so as to perform an action. The action may vary depending on the person who uses the card. Thus, phenomena such as "my friend's monster is slow but mine is quick" may appear. Then, the user may feel a strong affinity for his or her own monster.

5: This embodiment utilizes differences in environmental conditions of the operation of making the code reading apparatus read the code printed on a card, therefore, different outcomes may be produced depending on the environmental condition. For example, an animal such as a mole may not appear if the code is read in an environment where external light is rich. Similarly, if types of the monster include icy type, fire type, grass type, etc., the icy type monster may become strong when the location identified by a GPS is somewhere in the cold region or the observed temperature is very low.

6: With this embodiment, the entertainment system can be so designed as to make the card more powerful in initial stages, thereafter, weaker as the amount missing data by errors increases. Since the amount of missing data increases as the card is used,

10086422 "030102"

the animated monster may become more powerful as the card is used in initial stages but subsequently turn to be weaker and weaker as a result of aging.

7: If the code data is not obtained because of some error, the game program may be so designed that the game can be played differently depending on the amount and the breakdown of the errors. Then, errors that normally frustrate the user can be utilized as a source of entertainment.

10 [2nd Embodiment]

Now, the second embodiment of the invention will be described below.

The above described first embodiment is so arranged as to provide randomness according to the programs acquired in the course of a code reading operation. However, if the highest speed or the average speed of a moving of the code reading apparatus main body 100 or the recording medium 400 that can be estimated by the user are used as parameters without modifications, they may give not impress the user.

Therefore, this second embodiment is designed to enhance the level of randomness.

More specifically, the program ROM 201 of the application program storing cartridge 200, or the game cartridge, is made to store not the highest speed or the average speed of a moving but a number of speed patterns that show changes in the speed of the moving

as shown in FIG. 48. Then, the observed pattern of the changing speed is normalized to show a unit time the same as that of the speed patterns stored in the program ROM 201 and checked for matching sequentially with the stored patterns so as to select the matching pattern as parameter as shown in FIG. 49.

Alternatively, as shown in FIG. 50, a table from which parameter values that are not in a rising order or a falling order can be obtained according to the observed speed range may be stored in the program ROM 201 of the application program storing cartridge 200, or the game cartridge. The table may alternatively be stored in the code 401.

It may be appreciated that the above described arrangement may be applied not only to speed parameters, but also to any other parameters.

Thus, this second embodiment can provide an enhanced level of randomness.

While the present invention is described above by referring to preferred embodiments, the present invention is by no means limited to those embodiments, which may be modified or altered in various ways without departing from the scope of the invention.

For example, while the program processing apparatus 300 of the above embodiments is described as a portable game machine provided with an LCD, the technological concept of the present invention is not

limited thereto and the present invention is applicable to any video game machine or game that uses a personal computer. If this is the case, the data stored in the program ROM 201 of the application program storing cartridge 200, or the game cartridge, may be stored in the information storing medium of the video game machine, which may be a memory cartridge, a magnetic disk, a CD-ROM or a DVD (digital versatile disk) and the code reading apparatus main body 100 may be integrated with or externally connected to the game machine or the personal computer.

Additionally, while the above embodiments are described in terms of an electronic game of, for example, capturing and raising a monster, the technological concept of the present invention is by no means limited thereto and applicable to any game as long as it uses a playing card and an electronic game in combination.

Furthermore, there may be two or more identification codes of a character. If there are two or more types of card for the same character that illustrate different aspects of the character, the character may be provided with a plurality of identification codes.

Finally, the present invention is by no means limited to entertainment systems as in the case of the above described embodiments and may equally be applied

to educational equipment or other systems.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the present invention in its broader aspects is not limited to the specific details, and representative devices shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

5

10

10086422-030402